



MATERIAL SAFETY DATA SHEET

Page 1 of 5

HE78060 - CM-100

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 04/03/2009 Product Name: HE78060 - CM-100 Product Code: HE78060 Product/Material Uses Waterproof mastic.	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
petroleum asphalt	8052-42-4		25 - 55
calcium carbonate	1317-65-3		35 - 60
inert ingredients			<Balance>
Substances in this product have been pre-registered in accordance with the REACH Regulation - (EC) No. 1907/2006. See Section 15 for additional information.			

EMERGENCY OVERVIEW	
CAUTION! Direct skin and eye contact may cause irritation. Appearance/Odor: Brown paste, mild hydrocarbon odor.	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling)
Skin Hazards May cause skin irritation and contact dermatitis upon prolonged contact.
Ingestion Hazards May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

HE78060 - CM-100**3. Hazards Identification - Continued****Inhalation Hazards**

Inhalation of vapors or mists may cause irritation of the nose and throat. Breathing airborne particles from sanding or grinding may cause irritation to the respiratory tract.

4. First Aid Measures**Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water. If irritation persists, seek medical attention.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: >212 °F

Lower Explosive Limit: not applicable

Upper Explosive Limit: not applicable

Fire And Explosion Hazards

During a fire, toxic and irritating gases may be generated.

Extinguishing Media

In case of fire, use water fog, dry chemical, CO₂, or alcohol foam.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable state and federal regulations. Avoid runoff to waterways and sewers.

7. Handling And Storage**Handling And Storage Precautions**

Keep containers tightly closed when not in use. Store in a cool, dry, well-ventilated area. Keep away from strong oxidizers, sparks, heat or open flame. Use only with adequate ventilation.

8. Exposure Controls/Personal Protection**Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields are recommended. Additional protection such as goggles or faceshield may be used to protect the face from splash or spray, depending on conditions of use.

HE78060 - CM-100

8. Exposure Controls/Personal Protection - Continued

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

None normally required. Airborne exposures to hazardous vapors, mists, or dusts may be generated by mechanical operations such as spraying, grinding, etc. The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health and safety professional. If required, use an appropriate NIOSH-approved half-face air purifying respirator with an organic vapor cartridge and pre-filter or a supplied air respirator.

Ingredient(s) - Exposure Limits

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)

9. Physical And Chemical Properties

Appearance

Brown paste

Odor

Characteristic, solvent odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: NA °F

Boiling Point: NE °F NE °C

Specific Gravity: 1.30 - 1.35

Percent Volatiles: NA

Vapor Pressure: not available

Vapor Density: >1

Solubility: insoluble

Viscosity: 60,000-100,000 cps

Evaporation Rate: NA

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Not expected to occur

Conditions To Avoid (Stability)

Keep away from ignition sources, heat, sparks and flames.

Incompatible Materials

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products

Toxic and irritating gases, CO and CO₂.

11. Toxicological Information

Chronic/Carcinogenicity

None

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.



MATERIAL SAFETY DATA SHEET

Page 4 of 5

HE78060 - CM-100


11. Toxicological Information - Continued	
<u>Ingredient(s) - Toxicological Data</u> calcium carbonate LD50 (oral-rat) : 6450 mg/kg	
12. Ecological Information	
13. Disposal Considerations Dispose in accordance with applicable federal, state and local government regulations. Avoid/prevent release to the environment.	
14. Transport Information Ground Not restricted IMDG Not restricted IATA Not restricted	
15. Regulatory Information	
<u>SARA Hazard Classes</u> Acute Health Hazard	
<u>SARA Section 313 Notification</u> This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. Asphalt: Acute Hazard	
<u>Ingredient(s) - State Regulations</u> petroleum asphalt New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard Massachusetts - Hazardous Substance New York City - Hazardous Substance calcium carbonate Pennsylvania - Workplace Hazard	
<u>Canadian Regulatory Information</u> This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. Class D, Div 2, Subdivision B - Materials Causing Other Toxic Effects, Toxic Material at greater than or equal to 1.0%	
<u>European Union (EU) Regulatory Information</u> REACH Pre-registration Information:	
Substance (CAS#)	Reference Number
Asphalt (8052-42-4)	05-2114366982-36-0000
Calcium Carbonate (1317-65-3)	05-2114501824-55-0000

HE78060 - CM-100

Right-To-Know (Pictograms)



NFPA



HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

MSDS Preparer Phone Number: (484) 923-2313

This MSDS Supersedes A Previous MSDS Dated: 12/02/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

HENRY COMPANY CANADA