



MATERIAL SAFETY DATA SHEET

Page 1 of 4

BHM100TS - HB MOD. PLUS G100 TACK SHEET

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 09/08/2008 Product Name: BHM100TS - HB MOD. PLUS G100 TACK SHEET Product Code: BHM100TS Product/Material Uses Roofing Membrane	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
asphalt, petroleum	8052-42-4		45 - 75
inert ingredients			<Balance>

EMERGENCY OVERVIEW

CAUTION! This product contains asphalt. Some asphalt contains sulfur compounds which may form hydrogen sulfide when heated or burned. At higher concentrations (above 10 ppm), hydrogen sulfide is extremely toxic by inhalation, may cause respiratory-tract irritation and respiratory failure, coma and death. Direct skin and eye contact may cause irritation.

Appearance/Odor:

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation - possible if product becomes airborne, but considered unlikely.
Eye Hazards Particles may cause eye irritation.
Skin Hazards May cause skin irritation and contact dermatitis upon prolonged contact.
Ingestion Hazards Not a probable route of exposure.
Inhalation Hazards Not a probable route of exposure under normal conditions of use.

BHM100TS - HB MOD. PLUS G100 TACK SHEET**4. First Aid Measures****Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

5. Fire Fighting Measures

Flammability Class: Non Flammable

Fire And Explosion Hazards

During a fire carbon monoxide, carbon dioxide, oxides of nitrogen and sulfur, hydrogen sulfide, and irritating and/or toxic gases may be generated.

Extinguishing Media

Carbon dioxide, water, or dry chemical.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations. Avoid release to waterways and sewers.

7. Handling And Storage**Handling And Storage Precautions**

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from heat sparks, or flame. Use only with adequate ventilation.

8. Exposure Controls/Personal Protection**Engineering Controls**

Use with adequate general and local exhaust ventilation.

Eye/Face Protection

Safety glasses with side shields recommended.

Skin Protection

Use with protective gloves and apron to prevent skin contact.

Respiratory Protection

None normally required. Respirator use may be required due to secondary operations such as cutting, sanding, buffing, etc. The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Asphalt fume

ACGIH TLV-TWA 0.5 mg/m³ (Inhalable fraction and vapor)

BHM100TS - HB MOD. PLUS G100 TACK SHEET

8. Exposure Controls/Personal Protection - Continued
<p><u>Ingredient(s) - Exposure Limits</u> asphalt, petroleum OSHA PEL-TWA 5mg/m³ ACGIH TLV-TWA 0.5mg/m³ (Benzene soluble aerosol)</p>
9. Physical And Chemical Properties
<p><u>Appearance</u> Flexible sheet</p> <p>Chemical Type: Mixture Physical State: Solid Boiling Point: 650-1000 °F 343-538 °C Specific Gravity: >1.0 Percent Volatiles: <0.5% Vapor Pressure: not applicable Vapor Density: not available pH Factor: not available Solubility: not available Evaporation Rate: not available</p>
10. Stability And Reactivity
<p>Stability: Stable Hazardous Polymerization: Not expected to occur</p> <p><u>Conditions To Avoid (Stability)</u> Extreme temperatures, open flames, and strong oxidants.</p> <p><u>Hazardous Decomposition Products</u> Decomposition not expected to occur if handled and stored properly.</p> <p><u>Conditions To Avoid (Polymerization)</u> Incomplete combustion</p>
11. Toxicological Information
<p><u>Chronic/Carcinogenicity</u> None of the ingredients present in this product, at concentrations equal to or greater than 0.1%, have been determined to be carcinogenic by IARC, NTP, OSHA, or ACGIH.</p> <p><u>Miscellaneous Toxicological Information</u> Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.</p>
12. Ecological Information
None identified.
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations.
14. Transport Information
Ground Not restricted
IMDG Not restricted

BHM100TS - HB MOD. PLUS G100 TACK SHEET


14. Transport Information - Continued
 IATA Not restricted

15. Regulatory Information

U.S. Regulatory Information
 Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - State Regulations
 asphalt, petroleum
 California - Proposition 65

Canadian Regulatory Information
 This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: Not classified or controlled.

<u>NFPA</u>	<u>HMIS</u>								
	<table border="1"> <tr> <td>HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td>FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td>REACTIVITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td style="text-align: center;"> </td> </tr> </table>	HEALTH	0	FLAMMABILITY	1	REACTIVITY	0	PERSONAL PROTECTION	
HEALTH	0								
FLAMMABILITY	1								
REACTIVITY	0								
PERSONAL PROTECTION									

16. Other Information

Revision/Preparer Information
 This MSDS Supersedes A Previous MSDS Dated: 09/08/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

HENRY COMPANY