

LEXCOR MATERIAL SAFETY DATA SHEET

DATE PREPARED: 03/30/10

(3 Pages)

MSDS No: BE005 (E)

SECTION 1 & 2 - PRODUCT INFORMATION AND COMPANY IDENTIFICATION

PRODUCT NAME

FIBREBOARD

Chemical Name: BP Natural Sheeting, BP Enermax, BP Sound Deadening Boards, BP Excell II

Chemical Formula: None

General Use: Used for flat roof systems, insulating sheeting and noise reduction on the exterior of studs in frame construction.

SUPPLIER NAME AND ADDRESS

Lexcor
52 Bramwin Court
Brampton, Ontario L6T 5G2
Tel: 905-792-8800 Fax: 905-792-8801

EMERGENCY TELEPHONE NUMBER:

CANUTEC 613-996-6666 (24 hours everyday)

Regulatory Information Number:

Tel: 1-800-268-2889

SECTION 3 - HAZARDOUS INGREDIENTS

None.

This product contains no ingredients which are considered hazardous or are listed on the Ingredient Disclosure List of the Hazardous Product Act. This product is primarily composed of wood shavings and sawdust. The fibres are bonded together with starch and rendered water resilient by the addition of paraffin wax.

SECTION 4 - PHYSICAL DATA

ODOUR: None

APPEARANCE: Rigid board, available in various sizes, common sizes are 4' x 8'

PHYSICAL STATE: Solid Boards

SPECIFIC GRAVITY: .Approximately 13 to 18 lb/ft³

DENSITY: 0.20 to 0.28

pH: 6.8

THICKNESS: Ranges from 7/16" to 2"

SECTION 5 - FIRE AND EXPLOSION DATA

FLASH POINT: None

CONDITIONS OF FLAMMABILITY: Difficult to ignite. When tested to CAN4-S102 its flame spread classification rating is about 70. Smoke development rating about 49 and fuel contribution rating about 53.

AUTO-IGNITION TEMPERATURE: Approximately 260 °C

COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide.

FIRE AND EXPLOSION HAZARDS: Difficult to ignite

EXTINGUISHING METHOD: Water spray, water fog, carbon dioxide, dry chemical

FIRE FIGHTING PROCEDURES: Fire may smolder, therefore care should be taken to ensure complete extinguishment.

SECTION 6 - REACTIVITY DATA

STABILITY: *Avoid exposing product to flames or to temperatures higher than 260 °C*

CONDITION OF REACTIVITY: *None*

INCOMPATIBILITY: *Not applicable*

HAZARDOUS DECOMPOSITION: *Carbon monoxide, carbon dioxide*

HAZARDOUS POLYMERIZATION: *Cannot occur.*

SECTION 7 - ENVIRONMENTAL AND DISPOSAL INFORMATION

If any of this material is spilled, pick it up as in a normal clean up operation. If the product is in the form of dust or in small pieces, sweep up or vacuum and place it in a suitable container for disposal. Dispose of container in an approved land-fill in accordance with local, provincial/state and federal regulations. Since it is not asphalt coated, it can be recycled to manufacture wood fibreboard.

SECTION 8 - HEALTH HAZARD DATA

TOXICITY DATA: *This product contains no ingredients which are considered hazardous.*

EFFECTS OF OVEREXPOSURE:

INHALATION: *Dust may cause irritation to upper respiratory tract.*

EYES: *Solid or dust particles may cause irritation or corneal injury due to mechanical action.*

SKIN: *Dust may cause irritation.*

INGESTION: *Unlikely due to physical state of product.*

NOTE: *Exposure to this product is not anticipated to cause adverse effects.*

SECTION 9 - FIRST AID

EMERGENCY AND FIRST AID PROCEDURES INFORMATION:

SKIN: *Wash gently in warm water using mild soap.*

EYES: *Irrigate immediately with water for at least 15 minutes. Contact physician if required.*

INHALATION: *Not applicable*

INGESTION: *Unlikely due to physical state of product.*

SECTION 10 - HANDLING PRECAUTIONS

VENTILATION: *Use adequate ventilation. When cutting with a saw use dust collector attached to the saw.*

RESPIRATORY PROTECTION: *In dusty environment, use approved dust respirator.*

SKIN PROTECTION: *If necessary, wear loose fitting clothes, closed at wrists and neck. Wear tight fitting gloves.*

EYE PROTECTION: *Use safety glasses or face shield especially when doing overhead work.*

SECTION 11 - ADDITIONAL INFORMATION

Since this product is a "Manufactured Article", Lexcor is not required by law to produce a Material Safety Data Sheet. This Material Safety Data Sheet is provided only as customer service information.

Reference: *The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.*

PREPARED BY: LEXCOR (A Division of Lexsuko Corporation) **TEL:** (905) 792-8800 **TOLL FREE:** 1-800-268-2889