

MATERIAL SAFETY DATA SHEETS

NAME OF PRODUCT :	EXPANDED POLYSTYRENE FOAM IZOLON
MANUFACTURER/VENDOR:	PRODUITS POUR TOITURES FRANSYL LTÉE
ADDRESS:	671 LEVEILLE STREET TERREBONNE QC. PHONE: (450) 492-2392 J6W 1Z9 FAX: (450) 492-5415

INGRÉDIENTS DANGEREUX :	NONE
-------------------------	------

PHYSICAL DATA:

SPECIFIC GRAVITY:	0.013-0.064
BOILING POINT:	N/A
PHYSICAL STATE:	SOLID FOAM
KG PER LITER SOLUBILITY IN WATER:	N/A

FIRE AND EXPLOSION HAZARDS:

FLASH POINT:	655° F
EXTINGUISHING MEDIA:	WATER, FOG ,CO ² ,
DRY CHEMICAL (ABC):	915° F
FIRE EMISSIONS:	DENSE BLACK SMOKE, CARBONE

REACTIVITY:

STABLE: X	INSTABLE:	CORROSIVE:
------------------	-----------	------------

INCOMPATIBLE PRODUCTS:	HYDROCARBONS, ETHER, AMINES, ALDEHYDES <i>(All of them are deteriorate foam)</i>
------------------------	---

TOXICOLOGICAL PROPERTIES:

INHALATION:	N/A
SKIN ABSORPTION:	N/A
INGESTION:	N/A
LC 50% (Lethal Concentration):	N/A
LD 50% (Lethal Dose):	N/A
SYMPTÔMS OF OVER-EXPOSURE:	N/A



MATERIAL SAFETY DATA SHEETS EXP. POLYST (CONTINUED)

EMERGENCY FIRST AID:

INHALATION:	N/A
SKIN CONTACT:	N/A
EYES CONTACT:	FLUSH LOOSE BEAD FROM EYES WITH WATER
INGESTION:	N/A

SPILL OR LEAK PROCEDURES:

CLEAN UP:	NORMAL GOOD HOUSEKEEPING
WASTE DISPOSAL	BURY IN APPROVED LANDFILL OR BURN IN AN ADEQUATE INCENERATOR WITH EXCESS OXYGEN.

PERSONAL PROTECTION:

VENTILATION:	ONLY REQUIRED DURING LARGE SCALE HOT WIRE FABRICATION PROCEDURE OR COMBUSTION
SKIN PROTECTION:	WEAR DUST MASK DURING SAVING OR SANDING OPERATIONS
SKIN PROTECTION:	N/A
EYES PROTECTION:	SAFETY GLASSES WHEN SANDING OR SAWING

PRÉCAUTIONS:

STORAGE HANDLING:	<ul style="list-style-type: none">- DO NOT STORE AT INTERMITTENT TEMPERATURES ABOVE 167° F- DO NOT EXPOSE TWO SOURCE OF IGNITION;- EXPOSURE TO UV LIGHT (SUN) FOR LONG PERIODS WILL RESULT IN SLOW DEGRADATION (DUSTING) AT SURFACE;- LARGE SCALE HOT WIRE OR COMBUSTION OPERATIONS (OVER 200° F), COULD CAUSE CORROSION OF VENTILATION DUCTS OVER EXTENDED TIME PERIOD (YEARS) DUE TO HYDROGEN BROMIDE.
-------------------	---

Revised: february 06

ULC APPROVAL AND ISO 9002 CERTIFICATION