

Firestone Building Products Company

Material Safety Data Sheet

July 15, 2008

Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name: ISO 95+

Chemical Name / Synonym: ISO 95+ Composite, ISO 95+ Nailbase, ISO 95+ Tapered, ISO 95+ GL

Chemical Family: Polyisocyanurate

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Building Products Company

Manufacturer's Address: 250 West 96th Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0

HMS Hazard Rating: Health 1, Flammability 1, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
n-Pentane	n-Pentane	109-66-0	0.05-5.5	TLV 600 ppm PEL 1000 ppm
Ethyldimethylmethane	Isopentane	78-78-4	4.5-9.9	TLV 600 ppm PEL 1000 ppm
Tris (monochloropropyl) Phosphate	None	13674-84-5	<5	None Established
Fibrous Glass	Fiberglass	None	<11	TLV 1 f/cc TLV 5 mg/m ³ (inhalable)
Nonhazardous as per 29 CFR 1910.1200.	None	None	>71	None Established

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Inhalation

Signs and Symptoms of Exposure: May cause irritation to the eyes, skin and respiratory tract. Inhalation of high vapor concentrations of pentanes used in this product may cause dizziness, headaches, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

Medical Conditions Aggravated by Exposure: The dust produced by reprocessing of this product may aggravate pre-existing respiratory diseases.

Chronic Effects: This product contains tris(monochloropropyl) phosphate, which may cause skin sensitization.

Carcinogenicity: Direct implantation of glass fibers into the lung tissue of laboratory animals has produced lung fibrosis and lung cancer. Human epidemiological studies of inhalation exposure have yielded negative results.
Continuous filament glass fibers is listed by IARC as a class 3, *unclassifiable as to carcinogenicity in humans*.

SECTION 4: FIRST AID MEASURES

First Aid Procedures: For eyes, hold eyelids open and wash with gentle stream of water for at least 15 minutes preferably at eyewash fountain. For skin contact, wash affected area thoroughly with soap and

Firestone Building Products Company

Material Safety Data Sheet

July 15, 2008

Page: 2

water when time permits. For inhalation, remove to fresh uncontaminated air.

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media:	Water spray, Alcohol foam, Carbon Dioxide, or Dry chemical.
Hazardous Combustion Products:	Carbon dioxide and carbon monoxide, phosphorus oxides, and phosphoric acid.
Recommended Fire Fighting Procedures:	Wear impermeable protective clothing and self-contained breathing apparatus. Toxic fumes and vapors may be evolved.
Unusual Fire and Explosion Hazards:	Emits dense, black smoke when burned. Certain operations such as grinding or cutting may lead to a buildup of dust suspended in air which can cause a dust explosion if ignited. Provide adequate ventilation and appropriate dust handling systems. Isopentane and n-pentane, highly flammable materials, may be present within this product.

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled:	None required
Precautions to Be Taken in Handling and Storing:	Keep away from heat, sparks, and open flames. Store in a cool, dry area. Applying to hot surfaces requires special precautions. Protect against dust that may be generated by reprocessing, altering or applying this product. Remove dust by vacuuming rather than blowing.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use in a well-ventilated location.
Respiratory Protection:	During reprocessing, altering, and/or applying this product, a NIOSH respirator may be required based upon the end user's airborne concentration evaluation.
Eye Protection:	Wear safety glasses with side shields when reprocessing, altering and/or applying this product.
Skin Protection:	Wear cotton or leather gloves when handling this product.
Other:	None required.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking or smoking and at the end of each shift. Wash contaminated clothing prior to reuse.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	White rigid cellular sheets/odorless.		
Flash Point:	Not Applicable	Lower Explosive Limit:	None
Method Used:	Not Applicable	Upper Explosive Limit:	None
Evaporation Rate:	Not Applicable	Boiling Point:	None
pH (undiluted product):	Not Applicable	Melting Point:	Unknown
Solubility in Water:	Insoluble	Specific Gravity:	Unknown

Firestone Building Products Company

Material Safety Data Sheet

July 15, 2008

Page: 3

Vapor Density:	Not Applicable	Percent Volatile:	Unknown
Vapor Pressure:	Not Applicable		

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	None known.

SECTION 10: TRANSPORTATION

Regulatory Agency:	Not Regulated
Proper Shipping Name:	Not Applicable
Hazard Classification:	Not Applicable
Identification Number:	Not Applicable
Labels Required:	Not Applicable
Other Requirements:	Not Applicable

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments:	Physiological effects given in Section 3 are for dust and fume that may be generated during the reprocessing, altering or application of this product. Facers of this product may be foil, kraft paper, fiberglass, perlite, wood, black felt, or a combination of these.
Date of Previous MSDS:	June 14, 2007
Changes Since Previous MSDS:	Address change in section 1; TLV change in section 2; carcinogenicity information in section 3.
Telephone Number for Additional Information:	(317) 575-7190

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, a subsidiary of Bridgestone Americas Holding, Inc. assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.