



2" Metal Plate

Firestone Item Number: W56RAC4180

DESCRIPTION:

2" Metal Plates are specifically designed to be used with Firestone All-Purpose, Heavy-Duty and Concrete Drive Fasteners in roofing system applications for attaching Firestone Reinforced Perimeter Fastening Strips as specified in Firestone Specifications and Details.

METHOD OF APPLICATION:

Position plates along the Reinforced Perimeter Fastening Strip as specified by Firestone Specifications and Details. Attach plates to roof deck using the appropriate length Firestone Fastener. Install plates with ribbed side up, showing the "Firestone" label.


PACKAGING:

1000 plates per carton
32 cartons per pallet

PRECAUTIONARY DATA:

1. Do not overdrive or underdrive fastener.
2. Plates are designed to anchor Reinforced Perimeter Fastening Strips (RPFS and QSRPFS) only.
3. Avoid field seams directly over insulation plates where possible.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



PRODUCT DATA

Property

Minimum Performance

Material:	Steel with a Galvalume® coating
Material Thickness:	.026" - .036" (.66 mm - .91 mm)
Diameter:	2" (51 mm)
Corrosion Resistance:	Meets FM No. 4470 criteria
Pull-Through Resistance:	400 lbf (181.4 kg) from center hole

Note: Galvalume® is a registered trademark of BIEC International, Inc.

LEED INFORMATION:

Post Consumer Recycled Content:	8%
Post Industrial Recycled Content:	17%
Manufacturing Locations:	Bryan, OH Cleveland, OH



Subject to the conditions of Approval when installed as described in the current edition of the FM Approval Guide

Firestone Building Products Company
A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com