



## SA Primer

**Firestone Item Number:**  
**5 Gallon Pail: W70RACSAP5**

**DESCRIPTION:**

SA Primer is designed to prime substrates prior to the application of MB Base SA where required by Firestone Specifications and Details. SA Primer must be applied with a solvent resistant roller.

**METHOD OF APPLICATION:**

Surfaces must be clean, dry, and free of foreign materials. Stir SA Primer thoroughly before and during use. Apply SA Primer at the rate of one gallon per 200 square feet (one liter per 4.9 square meters) to the substrate. Roller apply until the substrate surface becomes dark in color with no streaking or puddling. Roller apply SA Primer to all side and end laps.

Allow the primed surface to dry according to the touch-push test (usually less than 10 minutes) before applying MB Base SA. Prime all laps and complete seaming procedures per Firestone's Specifications and Details.

SA Primer is available in 5-gallon (19 liter) pails. Packaging: 45 5-gallon pails per pallet.

**PRECAUTIONARY DATA:**

1. Thinning is not allowed.
2. Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
3. Red caution labels are required when shipping.
4. For professional use only.
5. Use only in well-ventilated areas.
6. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
7. Do not apply with brushes or rags.
8. Mix thoroughly before and during use.
9. Refer to Material Safety Data Sheet (MSDS).

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



### PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Base:	Synthetic Rubber Polymers
Color:	Translucent Gray
Solvents:	Heptane, Toluene
Percent Solids:	16 - 18%
Viscosity:	Very thin, free flowing
Weight:	6.62 lb/gal (0.79 kg/L) (nominal)
Specific Gravity:	0.793 Nominal (H <sub>2</sub> O = 1)
Flash Point:	0.0 F (-17.8 C)
Volatile Organic Compound (V.O.C.) Content:	Not to exceed 5.55 lb/gal (664 g/L)

**SHELF LIFE:**

1. Shelf life of 12 months can be expected if stored in original unopened container at temperatures between 60F (15.6 C) and 80F (26.7C).
2. Shelf life will be shortened if exposed to elevated temperatures.

**STORAGE:**

1. Store in original unopened cartons at temperatures between 60F (15.6C) and 80F (26.7C).
2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for application.

SA Primer is protected by U.S. Patent No. 5,985,981.

**LEED INFORMATION:**

Post Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: South Bend, IN

**Firestone Building Products Company**  
 A Division of BFS Diversified Products, LLC  
 310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
 Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpcco.com](http://www.firestonebpcco.com)