



# QuickPrime Plus LVOC

Firestone Item Number: **W563587043**

## DESCRIPTION:

QuickPrime Plus LVOC is designed to clean and prime RubberGard EPDM membrane prior to application of QuickSeam products where required by Firestone Specifications and Details. QuickPrime Plus LVOC must be applied with a QuickScrubber or QuickScrubber Plus pad and handle when preparing RubberGard membrane to receive QuickSeam Tape products. It may also be used to clean membrane prior to the application of Lap Sealant LVOC. It is formulated to meet V.O.C. requirements of 2.13 lb/gal (250 g/L) maximum.

## METHOD OF APPLICATION:

Surfaces to be primed must be clean, dry, free of foreign materials and excess dusting agent. Clean with broom or rags if necessary.

Stir QuickPrime Plus LVOC thoroughly before and during use. Apply QuickPrime Plus LVOC to the EPDM surfaces with QuickScrubber or QuickScrubber Plus pad and handle using long back and forth strokes with moderate-to-heavy pressure along the length of the area until surfaces become black in color with no streaking or puddling. Allow the QuickPrime Plus LVOC surfaces to flash off completely according to the touch-push test (usually less than 30 minutes) before applying QuickSeam products or Lap Sealant LVOC. Complete QuickSeam product installation or Lap Sealant LVOC application in accordance with Firestone Specifications and Details.

## PRODUCT DATA

### Property

### Minimum Performance

Base:	Synthetic Rubber Polymers
Color:	Black
Solvents:	Hydrocarbon and Halogenated Solvents
Percent Solids:	9 - 10 %
Viscosity:	Very thin, free flowing
Weight:	9.55 lb/gal (1.14 kg/L) nominal
Specific Gravity:	1.146
Flash Point:	57.2° F (14° C) (Closed Cup Method)
Volatile Organic Compound (V.O.C.)	
Contents:	Not to exceed 2.1 lb/gal (250 g/L)

## COVERAGE RATE:

1. Coverage rate is 150 - 225 square feet per gallon (3.68 - 5.52 square meters per liter) one side.

## SHELF LIFE:

1. Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Shelf life will be shortened if exposed to elevated temperatures.

## STORAGE:

1. Store in original unopened cartons at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. When exposed to lower temperatures restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for immediate application.

## PRECAUTIONARY DATA:

1. Thinning is not allowed.
2. Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
3. Red caution labels are required when shipping.
4. For professional use only.
5. Use only in well ventilated areas.
6. Avoid contact with skin. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
7. Use only in conjunction with QuickScrubber or QuickScrubber Plus pad and handle. Do not apply with rollers, brushes or rags.
8. Mix thoroughly before and during use.
9. Refer to Material Safety Data Sheet (MSDS).
10. Keep out of reach of children.
11. Dispose as a hazardous waste in accordance with local, state and federal regulations.
12. Recommended cleaner is rubbing alcohol followed by soap and water.

**Note: QuickPrime Plus LVOC is protected by U.S Patent No. 5,985,981.**

## LEED INFORMATION:

Post Consumer Recycled Content: 0%  
Post Industrial Recycled Content: 0%  
Manufacturing Location: South Bend, IN

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

**Firestone**  
BUILDING PRODUCTS COMPANY

# QuickPrime Plus LVOC



Subject to the conditions of Approval  
when installed as described in the current  
edition of the FM Approval Guide



Cements and Coatings for Roofing Systems  
As to an External Fire Exposure Only  
61P2  
See UL Directory of Products  
Certified for Canada  
And UL Roofing Materials  
And Systems Directory  
R9516

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebppo.com](http://www.firestonebppo.com)