



QuickPrime Plus

Firestone Item Number:**1 Gallon Pail: W563587041****3-Gallon Pail: W563587044****DESCRIPTION:**

QuickPrime Plus is designed to clean and prime RubberGard EPDM membrane prior to application of QuickSeam products where required by Firestone Specifications and Details. QuickPrime Plus must be applied with a QuickScrubber or QuickScrubber Plus pad and handle when preparing RubberGard membrane to receive QuickSeam Tape products. It may also be used to clean membrane prior to the application of Firestone Splice Adhesive (SA-1065).

METHOD OF APPLICATION:**Preparation of Splicing Surfaces**

Splice surfaces must be clean, dry, and free of foreign materials and excess dusting agent. Clean with broom or rags to remove contaminates.

Stir QuickSeam Plus thoroughly before and during use. Apply QuickPrime Plus at the rate of 200 - 250 square feet per gallon (4.91-6.14 square meters per liter) per side to the splicing surfaces using the QuickScrubber or QuickScrubber Plus pad and handle. Use back and forth strokes with heavy pressure along the length of the splicing area, until membrane surfaces become dark gray in color with no streaking or puddling. Additional scrubbing is required at factory seams, areas of excess dusting agent, or other contaminated areas of the RubberGard membrane. Change pads every 200' (61 m).

When using the QuickScrubber or the QuickScrubber Plus pad and handle, factory seams require parallel as well as perpendicular application motions along the factory seam. Apply sufficient pressure on the QuickScrubber Plus pad and handle during application so the pad holder flattens to allow the total surface of the pad to contact with the RubberGard membrane.

Allow the surfaces to dry according to the touch-push test (usually less than 10 minutes) before applying QuickSeam products or SA-1065 Splice Adhesive. Complete seaming procedures per Firestone's Specifications and Details.

**PRODUCT DATA****Property****Minimum Performance**

Base:	Synthetic Rubber Polymers
Color:	Translucent Gray
Solvents:	Heptane, Toluene
Percent Solids:	16 - 18%
Viscosity:	Very thin, free flowing
Weight:	6.62 lb/gal (0.79 kg/L) (nominal)
Specific Gravity:	0.793 Nominal (H ₂ O = 1)
Flash Point:	0.0 °F (-17.8 °C)
Volatile Organic Compound (V.O.C.):	
Content:	Not to exceed 5.55 lb/gal (664 g/L)

SHELF LIFE:

1. Shelf life of 12 months can be expected if stored in original unopened container at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Shelf life will be shortened if exposed to elevated temperatures.

STORAGE:

1. Store in original unopened cartons at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for application.

COVERAGE RATE/PACKAGING:

1. 200 - 250 square feet per gallon (4.91 - 6.14 square meters per liter) one side (100-125 square feet per gallon both sides).

Coverage rates for various QuickSeam products are as follows:

3" QuickSeam Tape: 375-450 lf (114 - 137 m) per gal
6" QuickSeam Tape: 180-225 lf (55-68 m) per gal
7" QuickSeam Tape: 150-200 lf (46 - 61 m) per gal
6" QuickSeam Batten Cover: 300-375 lf (91-114 m) per gal
5" QuickSeam Flashing: 340-400 lf (104-122 m) per gal

2. QuickPrime Plus is available in 3-gallon (11.4 liter) and 1-gallon (3.8 liter) pails.
3. Packaging: 75 3-gallon pails or 216 1-gallon pails per pallet (1-gallon cans are packaged 4 per box).

PRECAUTIONARY DATA:

1. Thinning is not allowed.
2. Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
3. Red caution labels are required when shipping.
4. For professional use only.
5. Use only in well-ventilated areas.
6. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
7. Use only in conjunction with QuickScrubber or QuickScrubber Plus. Do not apply with rollers, brushes or rags.
8. Mix thoroughly before and during use.
9. Refer to Material Safety Data Sheet (MSDS).

Note: This primer is applied using the process covered by U.S. Patent No. 5,520,761.

QuickScrubber Plus is protected by U.S. Patent No. 5,976,292.

QuickPrime Plus is protected by U.S. Patent No. 5,985,981.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: South Bend, IN

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone
BUILDING PRODUCTS COMPANY

QuickPrime Plus



Subject to the conditions of Approval when installed as described in the current edition of the FM Approval Guide



Cements and Coatings for Roofing Systems As to an External Fire Exposure Only 61P2

See UL Directory of Products Certified for Canada And UL Roofing Materials And Systems Directory R9516

Firestone Building Products Company

A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com