



## QuickSeam Batten Cover

**Firestone Item Number:**

- 6" x 100' (152.4 mm x 30.5 m): W56RAC1616**
- 9" x 100' (228.6 mm x 30.5 m): W56RAC1619**
- 12" x 50' (304.8 mm x 15.2 m): W56RAC1612**

**DESCRIPTION:**

QuickSeam Batten Cover is a semi-cured EPDM and QuickSeam Tape laminate designed to cover and seal batten strips and as specified by Firestone Specifications and Details. The release paper has been perforated, resulting in centering marks on the tape which acts as a guide in the application of the QuickSeam Batten Cover.

**METHOD OF APPLICATION:**

Use QuickPrime Plus and QuickScrubber or QuickScrubber Plus pad and handle to clean and prime the membrane and metal components within the seaming area. Use the centering marks on the tape as a guide to apply the QuickSeam Batten Cover Strip over the batten strip. Refer to the application instructions for QuickSeam Batten Cover Strip supplied in each carton of product for specific information on its installation.

**PACKAGING:**

Width	Rolls/Carton	Cartons/Pallet
6"	2	36
9"	1	36
12"	1	36

**Note:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

**SHELF LIFE:**

- Shelf life of one year can be expected if stored in original container at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
- Shelf life will be shortened if exposed to elevated temperatures.

**QUICKSEAM TAPE:**

Property	Minimum Performance
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	.035" ± .005" (.89 mm ± .127 mm)
Width:	6-1/8" + 3/8", -0" (15.56 cm + .95 cm, -0 cm)

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



### PRODUCT DATA

**EPDM FLASHING:**

Property	Minimum Performance
Base:	EPDM
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Semi-cured
Thickness:	.040" (1.016 mm) min. - .007" (.178 mm) /+ .017" (.432 mm)
Width:	6" + 0", -1/8" (15.24 cm + 0 cm, -.32 cm)

**STORAGE:**

- Store in original unopened cartons indoors at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
- Do not store on the roof in direct sunlight or at temperatures above 100° F (37.78° C).
- When exposed to lower temperatures, restore to 60° F (15.6° C) and 80° F (26.7° C) prior to use.

**PRECAUTIONARY DATA:**

Refer to Material Safety Data Sheet (MSDS).

**Note:** QuickSeam Batten Cover is protected by U.S. Patent No. 5,242,727 and 6,426,129.

**LEED INFORMATION:**

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Locations:	Michigan Center, MI Prescott, AR



Subject to the conditions of Approval when installed as described in the current edition of the FM Approval Guide



Flashing Material for Roofing Systems As to an External Fire Exposure Only 61P2 See UL Directory of Products Certified for Canada And UL Roofing Materials And Systems Directory R9516

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebppo.com](http://www.firestonebppo.com)