



## QuickSeam Curb Flashing

**Firestone Item Number: W56RAC1623**

### DESCRIPTION:

QuickSeam Curb Flashing is 18" wide 60 gauge non-reinforced RubberGard membrane with 3" wide tape factory laminated along one edge. The 3" tape portion is used to splice the QuickSeam Curb Flashing to the roof membrane. The balance of the QuickSeam Curb Flashing is applied to the vertical surface with Firestone BA-2004 or Water-Based Bonding Adhesive to hold the membrane in place and terminated using an approved termination detail.

### METHOD OF APPLICATION:

Use Firestone QuickPrime Plus and QuickScrubber or QuickScrubber Plus pad and handle to clean and prime membrane area to receive tape. Refer to Firestone's instruction sheet for Firestone QuickSeam Curb Flashing which is included in each carton.

### PHYSICAL CHARACTERISTICS:

1. Superior ozone and ultraviolet resistance.
2. Remains flexible over wide temperature variations.
3. Excellent long term weathering qualities.
4. Application temperature range is between -10° F (-23° C) and 120° F (49° C).

### PACKAGING:

50' rolls, 1 roll per carton  
24 Cartons per pallet

**Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.**

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



## PRODUCT DATA

### QUICKSEAM TAPE

Base:	Rubber Polymers
Color:	Black
Solvents:	None
Solids:	100%
Cure State:	Cured
Thickness:	.030" ± .005" (.762mm ± .127mm)
Width:	3" (77 mm)

### MEMBRANE

Base:	EPDM
Color:	Black
Solvents:	None
Cure State:	Cured
Thickness:	.060" + .005"
Width:	18"
Type:	Non-reinforced

### SHELF LIFE:

Shelf life of one year can be expected if stored in original packaging at temperatures between 60° F (15.6° C) and 80° F (26.7° C). Shelf life will be shortened if exposed to higher temperatures.

### STORAGE:

1. Store in original unopened containers indoors at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 100° F (38° C) as material may become difficult to install and the shelf life shortened.
3. If exposed to temperatures below 50° F (10° C), restore to room temperature for easier installation.

### LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Locations:	Michigan Center, MI Prescott, AR

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)