



QuickSeam Joint Cover

Firestone Item Number: W56RAC1644

DESCRIPTION:

QuickSeam Joint Cover is uncured FormFlash laminated to QuickSeam Tape. A second 3" (76.2 mm) layer of tape is applied at the center and is a special uncured, flowable QuickSeam Tape compound. The QuickSeam Joint Cover conforms to irregular surfaces such as encountered at "T" joints readily providing an excellent seal.

QuickSeam Joint Covers are designed to cover and seal:

1. "T" joints formed by field seam intersections.
2. Joint covers for seams at change in plane on wall or curb flashings.
3. 2" (51 mm) seam plates for RubberGard MAX pipe penetration attachment layouts.
4. "T" joints formed by the installation of pre-fabricated pipe flashings over field or factory seams.
5. As a protection pad under sheet metal joints for EdgeGard or snap-on metal.

METHOD OF APPLICATION:

Mating surface to receive the QuickSeam Joint Cover must be free of dust, dirt, oil, water and other contaminants.

MEMBRANE PREPARATION:

Clean the RubberGard membrane using QuickPrime Plus and the QuickScrubber or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished seam. Allow to dry according to the touch-push test. Additional cleaning may be required to assure that the membrane is completely cleaned. (Caution: more cleaning is needed at factory seams.)

As an option, clean the RubberGard membrane using clean cotton cloths and Splice Wash SW-100 to remove all dusting agent, dirt and other contaminants that will affect the finished seam. Allow to dry. Brush apply SA-1065 Splice Adhesive over the RubberGard membrane to receive the QuickSeam Joint Cover. Allow to dry according to the touch-push test.

PRODUCT DATA

QUICKSEAM TAPE:

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Solids:	100%
Cure State	
Splice Tape:	Cured
3" (76.2 mm)	
Center Layer	Uncured and flowable
Thickness	
Splice Tape:	.030" ± .005" (.77 mm ± .13 mm)
3" (76.2 mm)	
Center Layer:	.037" ± .005" (.94 mm ± .13 mm)

FORMFLASH:

<u>Property</u>	<u>Minimum Performance</u>
Material:	Uncured FormFlash, conforming to RMA minimum specifications
Color:	Black
Size:	5.75" ± .125" diameter (146 mm ± 3.17 mm)
Thickness:	.030" ± .005" (.76 mm ± .13 mm)

QUICKSEAM JOINT COVER INSTALLATION:

- Step 1:** Remove the release paper from the joint cover, taking care not to touch the outside edges of the joint cover.
- Step 2:** Fold the joint cover in half. Position the center of the joint cover over the target point and mate the joint cover to the prepared surface.
- Step 3:** Roll the mated surface of the joint cover with a 2" (51 mm) silicone roller from the center outward working the joint cover into the step-off or irregularity.
- Step 4:** Install Seam Edge Treatment per Firestone Specifications and Details.

PHYSICAL CHARACTERISTICS:

1. FormFlash will cure when exposed to heat and over time.
2. Uncured 3" (76.2 mm) tape center layer will cure when exposed to heat and over time.

SHELF LIFE:

1. Shelf life of one year can be expected when stored at temperatures between 60° F (15.6° C) and 80° F (26.7° C) in original unopened carton.
2. Shelf life will be shortened if exposed to elevated temperatures.

STORAGE:

1. Store in original unopened containers indoors at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 100° F (37.8° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

PACKAGING:

100 QuickSeam Joint Covers/carton; 60 cartons per pallet

PRECAUTIONARY DATA:

1. Refer to the Material Safety Data Sheet (MSDS).

Note: QuickSeam Joint Cover is protected by U.S. Patent No. 5,204,148.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Locations: Prescott, AR



QuickSeam Joint Cover

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone Building Products Company
A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpc.com