



## QuickSeam Pipe Flashing

**Firestone Item Number: W563581063**

### DESCRIPTION:

QuickSeam Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. QuickSeam Pipe Flashings will fit various penetrations and must be cut to correct pipe diameter before installation.

QuickSeam Pipe Flashings may be used to flash penetrations for both RubberGard EPDM as well as APP and SBS Modified Bitumen systems. On modified bitumen systems, a target patch of smooth APP or SBS material must first be installed per Firestone's requirements.

### METHOD OF APPLICATION:

Penetration must be clean of prior flashing and foreign materials. Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe. Install the Pipe Flashing, clamping ring and lap sealant per Firestone Specifications and Details.

### RUBBERGARD MEMBRANE PREPARATION:

Clean the Rubbergard membrane using QuickPrime Plus and a QuickScrubber or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished bond. Allow to dry according to the touch-push test. Remove the release paper. Install the pipe flashing and roll the flange with a silicone hand roller. Install the clamping ring and Lap Sealant per Firestone Specifications and Details.

### MODIFIED BITUMEN MEMBRANE PREPARATION:

**Install per specific requirements as outlined on the QuickSeam Pipe Flashing Technical Information Sheet located in the Firestone Asphalt Technical Manual.**

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



## PRODUCT DATA

### MOLDED PIPE FLASHING

<u>Property</u>	<u>Minimum Performance</u>
Material:	Molded EPDM
Color:	Black
Sizes:	Universal – Fits 1" O.D. to 6.875" O.D. (25.4 mm – 174.6 mm)
Clamp:	Stainless Steel - worm gear type (clamps are included)
Pipe Flange:	13" (33 cm) outside diameter
Thickness:	0.055" - 0.075" (1.4 mm - 1.9 mm)

### QUICKSEAM TAPE

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Percent Solids:	100%
Cured State:	Cured
Thickness:	.030" (.762 mm) + .005" (.13 mm)

Fits the Pipe Outside Diameters listed below:

1.000" - 1.375"	25.4 mm - 34.9 mm
1.625" - 1.875"	41.3 mm - 47.6 mm
2.000" - 2.625"	50.8 mm - 66.7 mm
2.750" - 3.625"	69.8 mm - 92.1 mm
4.000" - 4.500"	102.0 mm - 114.0 mm
5.000" - 5.563"	127.0 mm - 141.0 mm
6.000" - 6.875"	152.4 mm - 174.6 mm

**Note: For penetrations less than 1" in diameter, use Firestone QuickSeam Conduit Flashing.**

### PRECAUTIONARY DATA:

1. Refer to the Material Safety Data Sheet (MSDS).
2. Do not install over uneven substrates.

### LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Location:	Bensenville, IL

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpco.com](http://www.firestonebpco.com)