



QuickSeam R.M.A. Strip

Firestone Item Number:
W56RAC1611

DESCRIPTION:

QuickSeam R.M.A. Strip is a 10" (254.0 mm) wide RubberGard MAX membrane with two 3" (76.2 mm) wide strips of QuickSeam Tape factory laminated to it along its length. It is used for roof membrane attachment beneath the RubberGard membrane as additional membrane securement as specified in Firestone Specifications and Details. QuickSeam R.M.A. is also used for membrane attachment in Firestone's QuickBond MR System.

METHOD OF APPLICATION:

Roofing Attachment:

Unroll the QuickSeam R.M.A. Strip with the release paper up. Anchor the QuickSeam R.M.A. Strip using Firestone Seam Plates, V-Plates or batten strips and fasteners 12" o.c. max. (305 mm) per current Firestone Specifications and Details.

Position EPDM membrane over QuickSeam R.M.A. Strip with release paper in place and allow membrane to relax. Fold back EPDM membrane to expose the R.M.A. Strip. Prime the EPDM to be spliced to the tape using QuickPrime Plus and QuickScrubber or QuickScrubber Plus. Use touch-push test to determine when the QuickPrime Plus is ready to be mated to the tape. Remove the release paper. Roll the primed EPDM membrane onto the tape. Mate the membrane using a clean QuickScrubber Plus Handle and Pad, then roll the EPDM membrane over the QuickSeam R.M.A. Strip with a 1-1/2" (38.1 mm) wide silicone hand roller to ensure proper adhesion. Refer to installation instructions for specifics.

SHELF LIFE:

1. Shelf life of one year can be expected when stored at 60° F (15.6° C) to 80° F (26.7° C) in original unopened cartons indoors.
2. Shelf life will be shortened if exposed to elevated temperatures.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



PRODUCT DATA

QUICKSEAM TAPE:

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Percent Solids:	100%
Specific Gravity:	98 ± .02 (H2O = 1)
Cure State:	Cured
Thickness:	.025" ± .007" (.63 mm ± .18 mm)
Width:	3.00" - 0"/+ .125" (76.2 mm - 0/+ 3.2 mm)

RUBBERGARD MAX EPDM:

<u>Property</u>	<u>Minimum Performance</u>
Base:	EPDM
Color:	Black
Solvents:	None
Thickness:	.050 (1.26 mm) minimum ± 20%
Width:	10.00" + 0"/- .125" (254.0 mm + 0/-3.2 mm)

Note: Refer to Technical Information Sheet for RubberGard MAX for additional information.

STORAGE:

1. Store in original unopened cartons at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 100° F (37.8° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

PACKAGING:

100' (30.5 m) roll, 1 roll per carton; 36 cartons per pallet

Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

ENVIRONMENTAL IMPACT:

Post Consumer Content: 0%
 Post Industrial Content: 0%
 Manufacturing Location: Michigan Center, MI

Firestone Building Products Company
 A Division of BFS Diversified Products, LLC
 310 E. 96th Street, Indianapolis, IN 46240
 Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpc.com