



QuickSeam Reinforced Perimeter Fastening Strip

Firestone Item Number: W56RAC1632

DESCRIPTION:

QuickSeam Reinforced Perimeter Fastening Strip is a 6" (152.4 mm) wide RubberGard MAX membrane with 3" (76.2 mm) wide QuickSeam Tape factory laminated to it along one edge. It is used for non-penetrating flashings as specified in Firestone Specifications and Details.

METHOD OF APPLICATION:

Unroll the QuickSeam Reinforced Perimeter Fastening Strip (QSRPF Strip) with the release paper up and the tape portion farthest away from the wall or penetration. Anchor QSRPF Strip using Firestone 2" Seam Plates and fasteners 12" o.c. max. (305 mm) per current base tie-in details.

Attachment option: QSRPF Strip may be fastened with metal or polymer batten strips to the deck (in the mechanically-attached and fully adhered systems only) or fastened into the wall (metal battens only). Polymer batten may be used to fasten into wood sheathed parapet walls. Refer to appropriate Firestone details for specifics.

Position EPDM membrane over QSRPF Strip with release paper in place and allow membrane to relax. Fold back EPDM membrane to expose the tape. Prime the EPDM to be spliced to the tape using QuickPrime Plus and QuickScrubber or QuickScrubber Plus pad and handle per current procedures. Use touch-push test to determine when the QuickPrime Plus is ready to be mated to the tape. Remove the release paper. Roll the primed EPDM membrane into the tape. The portion of the QSRPF without tape may be bonded to the membrane using BA-2004 or Water-Based Bonding Adhesive, or SA-1065 Splice Adhesive. Roll the EPDM membrane over the QSRPF Strip with a 1-1/2" (50.8 mm) wide silicone hand roller to ensure proper adhesion. Refer to installation instructions for specifics.

SHELF LIFE:

1. Shelf life of one year can be expected when stored at 60° F (15.6° C) and 80° F (26.7° C) in original unopened cartons indoors.
2. Shelf life will be shortened if exposed to elevated temperatures.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

PRODUCT DATA

QUICKSEAM TAPE:

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Percent Solids:	100%
Specific Gravity:	98 ± .02 (H2O = 1)
Cure State:	Cured
Thickness:	.030" ± .007" (.77 mm ± .18 mm)
Width:	3.00" - 0", + .125" (76.2 mm), - (0 mm), + (3.2 mm)

RUBBERGARD MAX EPDM:

<u>Property</u>	<u>Minimum Performance</u>
Base:	EPDM
Color:	Black
Solvents:	None
Percent Solids:	100%
Cure State:	Semi-Cured
Thickness:	.060 (1.52 mm) ± 10%
Width:	6.00" - 0", + .125" (152.4 mm) - (0 mm), + (3.2 mm)
Breaking Strength:	80 lbf (355.9 N)

Note: Refer to Technical Information Sheet for RubberGard MAX EPDM for additional information.

STORAGE:

1. Store in original unopened cartons at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 100° F (37.8° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

PACKAGING:

100' (30.5 m) rolls, 2 rolls per carton; 21 cartons per pallet

Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Locations:	Prescott, AR

Firestone Building Products Company
A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com