



## QuickSeam Splice Tape

### Firestone Item Number:

- 3": W56RAC1603
- 6": W56RAC1626
- 7": W56RAC1617

### DESCRIPTION:

Firestone 3" (76.2 mm), 6" (152.4 mm) and 7" (177.8 mm) QuickSeam Splice Tape is designed for field splicing of RubberGard membrane panels and flashing.

### METHOD OF APPLICATION:

Use QuickPrime Plus and a QuickScrubber or QuickScrubber Plus pad and handle to clean and prime mating surfaces. Refer to the Firestone Installation Instruction Sheet for Firestone QuickSeam Splice Tape (included in each carton) and Firestone Specifications and Details.

### SHELF LIFE:

1. Shelf life of one year can be expected when stored in original container at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Shelf life will be shortened if exposed to elevated temperatures.

### PHYSICAL CHARACTERISTICS:

1. Excellent moisture resistance.
2. Excellent resistance to heat and cold.
3. Excellent green tack.

### PACKAGING:

3" (76.3 mm) 100' (30.48 m) rolls, 6 rolls per carton  
 6" (152.4 mm) 100' (30.48 m) rolls, 2 rolls per carton  
 7" (177.8 mm) 100' (30.48 m) rolls, 2 rolls per carton  
 40 cartons per pallet

**Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.**

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

## PRODUCT DATA

Property	Minimum Performance
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	0.030" (0.77 mm) ± 0.005" (0.127 mm)
Width and Length:	3" (76.3 mm) wide by 100 lf (30.48 m) 6" (152.4 mm) wide by 100 lf (30.48 m) 7" (177.8 mm) wide by 100 lf (30.48 m)

### STORAGE:

1. Store in original unopened containers indoors at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 80° F (26.7° C).
3. When exposed to lower temperatures; restore to room temperature prior to use.

### PRECAUTIONARY DATA:

Refer to Material Safety Data Sheets (MSDS).

### LEED INFORMATION:

Post Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Prescott, AR



Subject to the conditions of Approval when installed as described in the current edition of the FM Approval Guide



Membrane Splicing Tape for Roofing Systems  
 As to an External Fire Exposure Only  
 61P2  
 See UL Directory of Products  
 Certified for Canada  
 And UL Roofing Materials  
 And Systems Directory  
 R9516

**Firestone Building Products Company**  
 A Division of BFS Diversified Products, LLC  
 310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
 Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)