



## QuickSeam Walkway Pad

**Firestone Item Number: W56RAC1860**

### DESCRIPTION:

QuickSeam Walkway Pads are high quality rubber walkway pads with QuickSeam Tape factory laminated to the bottom. The QuickSeam Tape secures the walkway pads to the primed RubberGard membrane.

QuickSeam Walkway Pads help protect the membrane from damage due to necessary rooftop service traffic. The material incorporates excellent levels of hardness, tensile strength, tear resistance, wear and displays excellent cold flexibility. The owner is responsible for maintaining walkways in specific areas:

1. At all access points (ladders, hatches, doorways, etc.) to the roof.
2. Around all mechanical equipment which will require maintenance.
3. As a walkway system on roofs subjected to traffic more frequently than once per month.

### METHOD OF APPLICATION:

Position the QuickSeam Walkway pads so that the flat surface is over the completed RubberGard membrane, spacing each pad a minimum of 1" (25.4 mm) and a maximum 6" (152.4 mm) from each other to allow for drainage. If the installation of QuickSeam Walkway Pads over field fabricated seams or within 3" (76.2 mm) of a lap edge can not be avoided, the seam must be stripped in using 6" (152.4 mm) QuickSeam Batten Cover. The QuickSeam Batten Cover must extend beyond the walkway pad a minimum of 6" (152.4 mm) each side of the pad.

Use QuickPrime Plus and a QuickScrubber or QuickScrubber Plus pad and handle to clean and prime the RubberGard membrane. Allow QuickPrime Plus to dry according to the touch-push test. Remove the release paper on the tape and place the taped walkway pad into place on the primed membrane. Walk on the pad to assure proper overall adhesion.



## PRODUCT DATA

### WALKWAY PAD

<u>Property</u>	<u>ASTM Test Method</u>	<u>Min. Performance</u>
Base:		Rubber Polymers
Elongation, %, min.	ASTM D-412	
Parallel to grain flow	(Die C)	75
Perpendicular to grain flow	(Die C)	75
Brittleness Temperature	ASTM D-2137	-40 °F (-40 °C)
Hardness Shore A	ASTM D-2240	60 ± 5

### QUICKSEAM TAPE

<u>Property</u>	<u>Min. Performance</u>
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Percent Solids:	100%
Cure State:	Cured
Thickness:	.030" ± .005" (.77 mm ± .13 mm)

### Physical Characteristics

1. Pad size is 30" x 30" x .300" thick (76.2 cm x 76.2 cm x .762 cm thick).
2. QuickSeam Tape is factory laminated to walkway pads: 3 rows of 3" (76.2 mm) wide tape, or two rows of 7" (177.8 mm) wide tape.

### PRECAUTIONARY DATA:

1. When installing walkway pads on a ballasted system, additional ballast must be added around pads to maintain 10 lb/sq ft (48.82 kg/sq m).
2. Do not install walkway pads within 10' (3.05 m) of a roof edge when used in conjunction with ballasted systems. Concrete paving stones must be used in these areas.
3. Do not expose to open flame or ignition source.
4. Primers may have an adverse affect on styrene insulations.

**SHELF LIFE:**

1. Shelf life of one year can be expected when stored at 60° F (15.6° C) and 80° F (26.7° C) in original unopened packaging indoors.
2. Shelf life will be shortened if exposed to elevated temperatures.

**STORAGE:**

1. Store in original unopened packaging on a flat surface at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 80° F (26.7° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

**PACKAGING:**

50 QuickSeam Walkway Pads per pallet - 445 lb (201.9 kg)/pallet

**Note: QuickSeam Walkway Pads are covered by U. S. Patent No. 6,080,458.**

**LEED INFORMATION:**

Post Consumer Recycled Content: 0%  
Post Industrial Recycled Content: 0%  
Manufacturing Locations: Guelph, ON – Canada  
Wapakoneta, OH - USA



# QuickSeam Walkway Pad

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpco.com](http://www.firestonebpco.com)