



Single-Ply QuickPrime™ Primer

Firestone Item Number: W56358704A

PRODUCT DESCRIPTION:

Single-Ply QuickPrime Primer is a solvent based primer designed to clean and prime RubberGard™ EPDM membranes (Standard, PLATINUM™, MAX™, and EcoWhite™) and UltraPly™ TPO membranes to receive QuickSeam™ tape products/accessories where allowed by Firestone specifications and in accordance with state regulations.

APPLICATION DIRECTIONS:

1. Mix thoroughly before and during use. Product will appear as a fine dispersion after mixing.
2. Do not thin.
3. Splice surfaces must be clean, dry and free of foreign materials and excess dusting agent. Clean with broom or rags to remove contaminants.
4. Apply Single-Ply QuickPrime Primer at the **coverage rate of 200 - 250 ft²/gallon (5 – 6 m²/L) per side** to the splicing surfaces using the QuickScrubber™ or QuickScrubber Plus pad and handle. Use back and forth strokes (four minimum) with heavy pressure along the length of the splicing area, until membrane surfaces become uniform in color, with no streaks or puddles. Additional scrubbing is required where the substrate is contaminated.
5. Bear down on the QuickScrubber Plus pad and handle system during application so the pad holder flattens to allow the total surface of the pad to contact with the substrate to receive Single-Ply QuickPrime Primer.
6. Allow the surfaces to dry completely before applying QuickSeam products. Complete seaming procedures per Firestone's current specifications and details.
7. Contact your Firestone Technical Coordinator at 1-800-428-4511 for specific application information.

SHELF LIFE:

- Shelf life of 12 months can be expected if stored in original unopened container at temperatures between 60 °F – 80 °F (16 °C – 27 °C).
- Shelf life will be shortened if exposed to elevated temperatures

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



PHYSICAL PROPERTIES:

<u>Property</u>	<u>Minimum Performance</u>
Base:	Synthetic Rubber Polymers
Color:	Translucent
Solvents:	Aliphatic Petroleum Distillates Toluene
Percent Solids:	15% (nominal)
Viscosity:	Very Thin, Free Flowing
Density (nominal):	6.50 lb/gal (780 g/L)
Specific Gravity (nominal):	0.78 (H ₂ O=1)
VOC Content:	645 g/L (5.4 lb/gal)

PACKAGING:

UltraPly TPO QuickPrime LVOC Primer is available in:
3-gallon (11.4 liter) pail

STORAGE:

- Store in original unopened container indoors at temperatures between 60 °F – 80 °F (16 °C – 27 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate application.

PRECAUTIONARY DATA:

- **WARNING! Flammable!** Keep away from fire (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
- Keep away from children.
- For professional use only.
- Use only in well ventilated areas.
- Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
- Do not thin.
- Mix thoroughly before and during use.
- Use only in conjunction with QuickScrubber or QuickScrubber Plus. Do not apply with rollers, brushes or rags.
- Refer to Material Safety Data Sheet for additional precautionary data.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Michigan Center, MI
 VOC Content: 645 g/L



Firestone Building Products Company, LLC
 250 W. 96th Street, Indianapolis, IN 46260
 Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebppo.com



S723-RFS-248