



UltraPly™ TPO Coated Metal

Firestone Item Number: W56TPO3023

DESCRIPTION:

Firestone UltraPly™ TPO Coated Metal is made from a flexible non-reinforced thermoplastic polyolefin membrane factory laminated to hot-dipped galvanized steel. Firestone UltraPly TPO Coated Metal can function as a flashing component for the Firestone UltraPly TPO System.

METHOD OF APPLICATIONS:

1. Install UltraPly TPO coated Metal with 1/8" to 1/4" (3- 6 mm) between adjoining section.
2. Install 2" (5 cm) wide duct tape over joints in UltraPly TPO Coated Metal.
3. Heat Weld a 6" (15 cm) wide piece of UltraPly TPO Unsupported Flashing over the joint.
4. All welds to UltraPly TPO Coated Metal must be at least 1 1/2" (3.8 cm).

PHYSICAL PROPERTIES:

Color:	White
Back Color:	Galvanized
TPO Coating:	Thickness: 24 gauge metal G-90 hot dipped galvanized steel
Sheet Metal:	Thickness: .023" (.58 mm) min. G-90 hot dipped galvanized steel
Dimensions:	48" x 120" (4' x 10') (1.2 m x 3.1 m) 1/2" width ± 3/4" length
Weight:	44 lb (20 Kg) per sheet

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

PRODUCT DATA

STORAGE:

1. Store material in original unopened packaging away from sources of physical damage or chemical contamination.

PACKAGING AND STORAGE:

1. 10 or 30 sheets per pallet.
2. Store in a dry area with protective packaging intact.

LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Location:	Indianapolis, IN

Firestone Building Products Company
A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpc.com