



## TPO QuickSeam Flashing

**Firestone Item Number:**  
**W56TPO30T7 (White Flashing)**  
**W56TPOG0T7 (Gray Flashing)**  
**W56TPO0T7 (Tan Flashing)**

**DESCRIPTION:**

TPO QuickSeam Flashing is a nominal 30 mil TPO membrane laminated to a 35 mil, white cured seaming tape. TPO QuickSeam Flashing is used for flashing applications as indicated in the Firestone TPO Technical Manual.

**METHOD OF APPLICATION:**

Use Firestone TPO QuickPrime and QuickScrubber or QuickScrubber Plus to clean and prime membrane and metal mating surfaces. Refer to Firestone Installation Instruction Sheet for Firestone TPO QuickSeam Flashing.

**PHYSICAL CHARACTERISTICS:**

1. Excellent moisture resistance.
2. Excellent resistance to heat.
3. Excellent green tack.
4. TPO QuickSeam Flashing is packaged in 100' (30.5 m) rolls.
5. TPO QuickSeam Flashing is moldable on gravel stop flanges and joints.

**TECHNICAL SPECIFICATIONS – TAPE:**

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymer
Color:	White
Percent Solids:	100%
Specific Gravity:	98 ± .02 (H <sub>2</sub> O = 1)
Cure State:	Cured
Thickness:	0.035" (0.889 mm), +0.002" (0.051 mm), -0.005" (0.127 mm)
Width:	5-3/4" (146 mm) - 0 (-0 mm), + 1/16" (-1.65 mm)
Length:	100 Lineal Feet (30.5 m) -0 (-0 m), + 2' (.61 m)

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

### PRODUCT DATA

**TECHNICAL SPECIFICATION – TPO FLASHING:**

<u>Property</u>	<u>Minimum Performance</u>
Base:	TPO
Color:	White, Gray, Tan
Solvents:	None
Percent Solids:	100%
Specific Gravity:	1.15 ± .05
Thickness:	.030" (.76 mm) ± 10%
Width:	5-1/2" (140 mm) + 0" (+0 mm), -1/8" (-3.18 mm)
Length:	100 Lineal Feet (30.5 m) ± -0 (-0 m), + 2' (.61 m)

**SHELF LIFE:**

1. Shelf life of 6-9 months can be expected when stored at 60° F (15.6° C) to 80° F (26.7° C) in original unopened containers indoors.
2. Shelf life will be shortened if exposed to elevated temperatures.

**STORAGE:**

1. Store in original unopened containers indoors at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store on roof in direct sunlight or at temperatures above 80° F (26.7° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

**PRECAUTIONARY DATA:**

1. Refer to Material Safety Data Sheets.

**LEED INFORMATION:**

Post Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Michigan Center, MI

**Firestone Building Products Company**  
 A Division of BFS Diversified Products, LLC  
 310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
 Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)