



## Metal Batten Strip

**Firestone Item Number: W56RAC3053**

### DESCRIPTION:

Metal Batten Strip is specifically designed to be used for anchoring RubberGard membrane and flashing details as specified in Firestone Specifications and Details.

### METHOD OF APPLICATION:

Attach batten strips to the roof substrate or penetration using the appropriate Firestone Fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

### STORAGE:

Store in original unopened container protected from the weather.

### PACKAGING:

50 - 10' pieces (3.05 meter pieces) per cardboard tube

### PRECAUTIONARY DATA:

1. Do not overdrive or underdrive fastener.
2. All cut surfaces must be rounded and filed to remove burrs and sharp edges.
3. Batten strips should be stored in the original Firestone shipping container until ready to use.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

## PRODUCT DATA

### Property

### Minimum Performance

Material:	Galvalume® AZ 55
Corrosion Resistance:	Meets FM No. 4470 criteria
Length:	10' (3.05 Meters)
Width:	1.0" (25.4 mm)
Thickness:	.0448"/.0508" (1.13 mm/1.29 mm)
Holes:	.280" (7.11 mm) diameter, at 6" (152 mm) o.c.

### LEED INFORMATION:

Post Consumer Recycled Content:	8%
Post Industrial Recycled Content:	17%
Manufacturing Location:	Cleveland, OH



Subject to the conditions of Approval when installed as described in the current edition of the FM Approval Guide

**Firestone Building Products Company**  
A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpco.com](http://www.firestonebpco.com)