



Coiled Metal Batten Strip

Firestone Item Number: W56RAC3052

DESCRIPTION:

Coiled Metal Batten Strip is specifically designed to be used for anchoring RubberGard membrane and flashing details as specified in Firestone Specifications and Details. Coiled Metal Batten Strip is packaged in a weather-resistant cardboard dispensing package which contains 220 feet (67 m) of batten strip. Using Coiled Metal Batten Strips in lieu of conventional pre-cut strips reduces labor and storage space. Coiled Metal Batten Strip has 3" o.c. pre-punched holes for greater flexibility in attaching to steel decks.

METHOD OF APPLICATION:

Attach batten strips to the roof substrate or penetration using the appropriate Firestone Fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

STORAGE:

Store in original unopened containers protected from the weather.

PACKAGING:

220 feet (67 m) per coil
52 coils per pallet

PRECAUTIONARY DATA:

- When cutting battens, round ends and remove burrs and sharp edges with a file.

Galvalume® is a registered trademark of BIEC International, Inc.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Material:	Galvalume® AZ 55
Corrosion Resistance:	Meets FM No. 4470 criteria
Length:	220' (67 m) per coil
Width:	1.0" (25.4 mm)
Thickness:	.0448"/.0508" (1.13 mm/1.29 mm)
Holes:	.344" (8.74 mm) diameter 3" (76.2 mm) o.c. (Accommodates Firestone All-Purpose, Heavy-Duty, Heavy-Duty Plus and Concrete Drive Fasteners)
Weight:	32 lb (14.5 kg) per coil

LEED INFORMATION:

Post Consumer Recycled Content: 8%
Post Industrial Recycled Content: 17%
Manufacturing Location: Cleveland, OH



Subject to the conditions of Approval
when installed as described in the current
edition of the FM Approval Guide

Firestone Building Products Company
A Division of BFS Diversified Products, LLC
310 E. 96th Street, Indianapolis, IN 46240
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com